



ROTARY

Fúrásí Zrt. ■ Drilling Co.Ltd.

A member of the  Group

KK-10

Workover Rig 375 HP
IDECO SBS DIR-5506

DEPTH RANGE:

2500 m with 2 7/8" DP, 3800 m with 3 1/2" Tubing

SUBSTRUCTURE:

Height: 3.8 m (12.7 ft)

Height under rotary beams: 3.0 m (9.8 ft)

Set Back: 95 mt

MAST:

IDECO-SBS KM 103-212 GH, 31.5 m (103 ft)

Capacity: 96.2 mt

CROWN BLOCK:

No of sheaves: 5

Grooved: 1"

Capacity: 120 mt

TRAVELLING BLOCK & HOOK:

IDECO shorty UTB-110-3-24

Capacity: 90,7 mt

SWIVEL:

IDECO TL-120

Capacity: 109 mt

DRAWWORKS:

H 37 ED IDECO 1"

Capacity: 375 HP

ROTARY TABLE:

LR-175, 17 1/2"

Capacity: 147 mt

RIG POWER SUPPLY:

Diesel Engines: 1 x CAT 3406 DITA

Capacity: 380 HP

MUD PUMPS:

1 x GD PAH-275 triplex, Powered by 3406 CAT



MUD TANKS:

Mud Tanks: Brine mixing tank 3 x 30 m³

Water tanks: 1 x 43 m³