



ROTARY

Fúrásí Zrt. • Drilling Co.Ltd.

A member of the  Group

SLU5

Truck mounted Double Drum Slickline Unit
Koller 31800589-10.000
Manufactured in 2018



TRUCK AND SUPERSTRUCTURE:

MAN TGS 23.360 6X6 BB chassis
24ft ISO Container design Swap Body, Double drum drawworks

POWER PACK:

Caterpillar C4.4 125 HP Euro 4

SLICKLINE DRUM:

Capacities min. in meter 16.600 at 0.108" line
Speed (at surface): OD 3 - 660 and ID 1-385 m/min
Max. Pulling force: OD 2.518 and ID 4. 317 kg

BRAIDED LINE DRUM:

Capacities min. in meter 11.000 at 3/16" line
Speed (at surface): OD 3 - 768 and ID 1-287 m/min
Max. Pulling force: OD 2.159 and ID 5.767 kg

PCE CONTROL PANEL:

5 function for dual hydraulic BOP, Line wiper-stuffing box, grease injection and wellhead pressure

MEASURING HEAD:

Benchmark "DOLPHIN" Slickline measuring device, heavy duty two wheeled which accurately measures both wireline depth and tension.

CONTROL PANEL- MEASURING SYSTEM:

Benchmark Universal Dual Touch Screen Panel 40 series
Benchmark Backup Digital Depth Panel ALS6A 100

