



ROTARY

Fúrásí Zrt. ■ Drilling Co.Ltd.

A member of the  Group

KK-23

Light Workover Rig 303 HP
IDECO SBS DIR-110

DEPTH RANGE:

2928 m with 2 7/8" Tubing

SUBSTRUCTURE:

Height: 3.8 m (12.5 ft)

Height under rotary beams: 2 m (6.56 ft)

Set Back: 50 mt

MAST:

IDECO-SBS KM 90-120 GHA, 27 m (88.5 ft)

Capacity: 54,4 mt

CROWN BLOCK:

No of sheaves: 4

Grooved: 1"

Capacity: 68 mt

TRAVELLING BLOCK & HOOK:

IDECO UTB 75-2-24

Capacity: 68 mt

SWIVEL:

IDECO TL-120

Capacity: 109 mt

DRAWWORKS:

IDECO –SBS H35-CK

Capacity: 303 HP

ROTARY TABLE:

LR-175, 17 1/2"

Capacity: 147 mt

RIG POWER SUPPLY:

Diesel Engines: 1 x CAT 3306 DITA

Capacity: 380HP

MUD PUMPS:

1 x GD PAH-275 triplex, Powered by 3408 CAT



MUD TANKS:

Mud Tanks: Brine mixing tank 2 x 20 m³

Water tanks: 1 x 43 m³