



# ROTARY

Fúrásí Zrt. ■ Drilling Co.Ltd.

A member of the  Group

## Lyb-40

Workover Rig 375 HP  
IDECO SBS DIR-5506

### DEPTH RANGE:

2500 m with 2 7/8" DP, 3800 m with 3 1/2" Tubing

### SUBSTRUCTURE:

Height: 3.8 m (12.7 ft)  
Height under rotary beams: 3.0 m (9.8 ft)  
Set Back: 95 mt

### MAST:

IDECO-SBS KM 103-212 GH, 31.5 m (103 ft)  
Capacity: 96.2 mt

### CROWN BLOCK:

No of sheaves: 5  
Grooved: 1"  
Capacity: 120 mt

### TRAVELLING BLOCK & HOOK:

IDECO shorty UTB-110-3-24  
Capacity: 90,7 mt

### SWIVEL:

IDECO TL-120  
Capacity: 109 mt

### DRAWWORKS:

H 37 ED IDECO 1"  
Capacity: 375 HP

### ROTARY TABLE:

LR-175, 17 1/2"  
Capacity: 147 mt

### RIG POWER SUPPLY:

Diesel Engines: 1 x CAT 3406 DITA  
Capacity: 380 HP

### MUD PUMPS:

1 x GD PAH-275 triplex, Powered by 3406 CAT



### MUD TANKS:

Mud Tanks: Brine mixing tank 3 x 30 m<sup>3</sup>  
Water tanks: 1 x 43 m<sup>3</sup>