

R-69

Drilling Rig 1000HP ZJ40 Truck-mounted

RATED DRILLING DEPTH:

3500 m (11,483 ft) with 5" DP 4000 m (13,123 ft) with 4 1/2" DP (not included 4 1/2" DP)

SUBSTRUCTURE:

DZ2225X01 Height: 6 m (19.7 ft) Height under rotary beams: 5 m (16.4 ft) Max load of rotary beam: 229 mt (505,820 lbs) Setback capacity: 137 mt (303,492 lbs)

MAST:

DSL, 38 m (125 ft) hydraulic telescopic, hydraulic lifting and lowering

Capacity: 229 mt (505,820 lbs)

CROWN BLOCK:

DSL

No of sheaves: 4+2 Grooved: 1 1/4"

Capacity: 229 mt (505,820 lbs)

TRAVELLING BLOCK & HOOK:

BENTEC TB-275-5-42-1 traveling block + Hook

No of sheaves: 5

Capacity: 250 mt (551 155 lbs)

SWIVEL:

XSL225

Capacity: 229 mt (505,820 lbs)

Max. working pressure: 350 bar (5000 psi) Equipped with integrated pneumatic Kelly spinner

DRAWWORKS:

JC28P/D (1000 HP)

Two pcs of CAT C18 engines, 630 HP each Brake: PZ40 hydraulic water-cooled disc brake Auxiliary brake: EATON WCB236 pneumatic watercooled PLC controlled disc brake

ROTARY TABLE:

ZP275, 27 1/2"

Capacity: 280 mt (617,294 lbs) Max. output torque: 27,500 Nm



TOP DRIVE:

BENTEC TD-250-C

Capacity: 227 mt (500 449 lbs)

Drilling torque: 47 750 Nm (35 200 ft lbs)

Drilling Speed: 0 to 200 1/min

Make up/ Brake out Torque: 60 000 Nm (44 254 ft lbs)

POWER PLANT:

Diesel engine driven gensets: 3 x CAT C-18-700,

Rated power prime: 635KVA/508 KW (2 x 680 HP, ϕ =0,8)

Rated voltage: 400/230 VAC

Phase: 3 phase

MUD SYSTEM:

Mud Pumps: 2 x Bomco F-1000 triplex, each pump powered by one diesel engine Caterpillar 3512 type, 2 x 764 kW (1024 HP)

Mud Tanks: 4 (Active mud tanks) + 1 (Reserve mud tank) + Trip Tank + Sand Trap, Total capacity: 180 m3 Shale Shaker: 2 x Swaco-Mongoose PT dual-motion

Capacity: 600 GPM each

Mud Cleaner: Swaco Combo D-sander/D-silter unit

Desander: 2x10" slant type Desilter: 12x4" single cone vertical

Degasser: Swaco Compact vacuum degasser unit Centrifuges: 1 pc Swaco 518 std. high speed